

# **NUSCAN 2700R 2D Wireless Barcode Scanner with Charging Cradle**



The Adesso Nuscan 2700R is the ultimate wireless barcode scanning solution. With its maximum scanning rate at 120 scans per second, users will find increase in their work efficiencies. The Nuscan 2700R's new decoding engine allows it to decode common 2D barcodes such as QR Code, PDF 417, and Data Matrix. It also scans common 1D barcodes. With the 2.4 GHz RF Wireless Technology, users will find connecting the scanner with your machine a breeze. Plug-n-Play, it's that simple.

# 2.4 GHz RF Wireless Technology

The wireless receiver allows the scanner to work up to 150 ft with no wires to get tangled.

## 2D Scanning Engine

The 2D scanning engine offers decoding capability for 2D barcodes like PDF417, Data Matrix, QR Code, MicroQR as well as common 1D barcodes.

## Spill Resistant

The scanner's spill resistant design helps to prevent fluids from staying inside, which would otherwise cause damage to the scanner.

# Superior Scanning Performance

Equipped with its CMOS sensor the device has a motion tolerance of 5 inches per second, offering fast and accurate scanning results.

# Charging Cradle with Built-In Receiver

This charging cradle allows for hands-free scans and charges the scanner at the same time. Its built-in USB receiver also makes the scanner completely Plug-n-Play!









SENSO 640 x 480 CMOS Superior Scanning

Performance

2.4GHz RF 2D Scanning Wireless Technology Engine

# **Operational Specifications:**

Picture Sensor Light Source Depth of Field System Interface Scan Rate Scan Pattern Minimum Resolution Supported Print Contrast Light Level Indicators **Environmental Sealing** System Interface **Electrical Specifications:** Input Voltage Working Current (USB) Working Current (serial) **Environment Specifications:** Working Temperature Working Humidity Physical Specifications: Dimension Weight

640\*480 CMOS 640 nm Visible -Red LED 0-12 inches (@20mil EAN-13, PC 100%) USB Wired/2.4Ghz Wireless , RS232 120 FPS Manual Scan, Auto Scan 40 mm 13 mil >25% 0-70000LUX Blue LED IP54 USB (USB-HID, USB-COM), RS232 5 + 5% VDC

280mA 288mA

-20° C to 55℃ 5% to 95% relative humidity, non-condensed

Linux, Android, Windows® 10/8/7/XP, Mac OS

6.61 x 3.34 x 2.44" (168 x 85 x 62mm) 0.22 lbs/100 g

Supported Symbologies

1D: EAN-8, EAN-13, EAN-13 2 add-on, EAN-13 5 add-on, ISSN, ISBN, UPC-A, UPC-E, Code11, Code 32 Code 39, Code 93, Code 128, Codabar, Industrial 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, GS1-128 GS1 Databar (RSS14), GS1 DataBar Limited, GS1 DataBar Expanded 2D: PDF417, MicroPDF417, MicroQR, Data Matrix, QR, Aztec

**USB & Serial Port** 

#### **Requirements:**

**Operating System** 

Connectivity Interface

- Includes:
- NuScan 2700R Scanner **Ouick Start Guide**

# Shipping Information:

Item	UPC Code	Box Dimensions	Box Wt.	Qty/Ctn
NuScan 2700R	783750010658	7.5 x 4.5 x 3.3″	1.31 lbs	10/40