

NuScan 7300CR **Adesso 2.4 GHz Wireless CCD Barcode Scanner**



■ 2.4 GHz RF Wireless Technology

The wireless receiver allows the scanner to work up to 100 ft. with no wires to get tangled.

■Superior Scanning Performance

The 500 scans per second scan rate and innovative high pixels CCD engine offers fast and accurate scanning results.

■ Drop Protection

With the scanner's CCD engine and durable silicone plastic material, it makes the Nuscan 7300CR less likely to become damaged due to accidental drops.

■Long Scanning Range

The CCD sensor is able to scan barcodes up to 20 inches scan depth.

■ Reliable Data Collection

Its built-in decoder can read the majority of 1D barcodes in existence and its driver-less operation makes it easy to use with both Windows and Mac operating systems.

■ Ergonomic Design

Easy-to-hold grip and a thumb-switch offers maximum comfort for long scanning use.



EAN-8/13, Codabars, Code 11, Code 39, Code 39 Full ASCII, Code 93, Code 128, GS1 DataBar Limited (RSS Limited), GS1 DataBar Omnidirectional (RSS Omnidirectional), UPC-A, UPC-E, Code 2 of 5 (ITF, Industrial, Matrix, Standard IATA), MSI, Plessy, Addedum 2 or 5.



Technology







Long Scanning

Specifications:

Mechanical **Scanner**

Dimensions: 166(L) x 88(W) x 73(H) mm 6.5 (L) x 3.5(W) x 3 (H) in.

Weight: 170±5g (without cable) Material: ABS+TPE+PC

Electrical

Power Input Voltage: 5 ± 0.25 VDC Working Current: $245 \pm 12 \text{ mA}$ Maximum Current: $317 \pm 16 \, \text{mA}$

Battery: 3.7V, 1500mAH, 18650 Polymer

Charging Time: 3 hrs

Light Source: LED, red, 632nm

Performance

USB Wired/Wireless 2.4GHz. Interface: 32 bit ARM Cortex-M3 MCU Microprocessor:

up to 100 ft. Wireless Range: Sensor: Linear CCD Sensor Resolution: 3mil @ PCS 90% Code 39

Depth of Field: up to 20 in. (@20 mil Code 39 PCS

90%)

Scan Rate: 500 scans per second

Scan Angle: Roll ±35°, Pitch ±65°, Yaw ±360°

Print Contrast:

Alert Operation: LED light indicator and beeper

Trigger Mode: Auto & Manual

Environmental

Operating Temp: 0-50°C (32-122°F) Storage Temp: -20-70°C (-4-158°F) Operating Humidity: 20-95% (Non-condensing) Storage Humidity: 20-95% (Non-condensing)

ESD Protection: 15KV **Shock Resistance:** 1.5m freefall IP Grade: >IP 54 EMI: N/A

Requirements:

Windows® 10, 8.1, 7, XP, & Mac® OS X **Operating System**

Interface USB or Wireless 2.4 GHz

Includes:

Adesso NuScan 7300CR 2.4GHz Wireless CCD Barcode Scanner Adesso NuScan 7300CR Charging Cradle

Quick Start Guide

Shipping Information:

Item	Connection	UPC Code	Box Dimensions	Box Wt.	Qty/Ctn
Nuscan 7300CR	Wireless 2.4GHz	783750007993	10.4" x 7.3" x 4.1"	1.4 lb.	10/40









