




www.adesso.com

NuPrint™ 330

3" (80mm) Network Interface Thermal Receipt Printer



Supports Network Interface



Supports 80 mm thermal paper



Up To 250MM Printing Speeds



Warning Sounds for Paper Jam, & Refill

Features

- Supports to print 3" (80mm) thermal paper
- Supports to print general 1D barcode and 2D (QR/PDF417) barcodes as needed
- Easy loading paper, out-off paper, with near-end sensor and black mark detection
- With 4K NV flash an 1M data buffer to strengthen printing speed and graphic printing and support multi languages with graphic (User defined) printing
- With autocutter and the reliability of cutter life is 1 million times and printer head life up to 150KM
- Supports re-print function, missing order printing and forbid lose order to print
- With Multi-Interface : Network Interface (RJ45), USB & Serial 232
- Compatible ESC/POS command
- Supports Windows , Linux OS systems and OPOS driver
- Water, oil splash and dust proof design
- Loud speaker and blue LED for reminder paper printing , error, lack of paper, without tearing paper warning
- Supports connection with cash drawer

Specifications:

Printing Method	Direct Thermal
Printing Speed	250mm/s
Paper Width	3.13"±0.2" (79.5±0.5mm)
Paper Diameter	3.15" (80mm)
Paper Thickness	0.06-0.08mm
Column Capacity	576 dots/line 384 dots/line
Line Speed	3.75mm (customizable with commands)
Character Size	ANK, Font A: 12x24 dots; Font B: 9x17 dots
Barcode Printing	1D: UPC-A /E, JAN13 (EAN13) JAN8, (EAN8), Code 39, Code 128, Code 93, Codabar ; 2D: PDF417, QR
Data Buffer	4KBytes (off page mode) 1M Input Buffer (page mode)

Autocutter	Half cut
Cutter Life	1 million cuts

Reliability:

Printing Head Life:	Up to 150KM
---------------------	-------------

Power:

Power Supply:	AC110V/220V 、 50~60Hz, DC 24V=2.5A
Cash Drawer Control :	DC 24V=1A

Interface:

Interface:	LAN + Serial RS232 + USB
------------	--------------------------

Environmental

Working Environment:	-4°~122°F (0°~45°C) Humidity (20-90%)
Storage Environment:	-14°~140°F (-10~60°C) Humidity (10-90%)

Physical

Dimensions:	7.6" x 5.7" x 5.6" (194 x 138 x 135 mm)
Weight:	3.75 lbs (1.13Kg)

Supports Characters

95 Alphanumeric, 19 International, 128x43 Graphics (including user-defined page), Traditional/Simple Chinese, Thai, Japanese, Korean

Requirements:

Operating System:	Windows® 2000 / XP / Vista / 7 / 8 / 10 / Linux / OPOS
Connectivity Interface:	USB+lan+serial

Includes:	NuPrint 330, Thermal Paper, Serial Cable, Power Cable USB Cable, Quickstart Guide
-----------	--

Shipping Information:

Item	UPC Code	Box Dimensions	Box Wt.	Qty/Ctn
NuPrint 330	783750012492	8.75" x 8.3" x 6.25"	5.8 lbs	8

